

Filtres déshydrateurs anti-acide Carly

Référence	Raccord		Puissance frigorifique (kW)				Capacité de fluide déshydratable (kg)					
	à visser	à souder	R22	R134	R404a R507	R407c R410a	R22 R407c		R134a R410a		R404a R507	
							24°C	52°C	24°C	52°C	24°C	52°C
DCY032	1/4		8.0	7.7	5.5	8.2	6.5	5.5	7.0	6.0	6.5	5.5
DCY032S		1/4	8.0	7.7	5.5	8.2	6.5	5.5	7.0	6.0	6.5	5.5
DCY033	3/8		22.0	20.0	15.0	22.5	6.5	5.5	7.0	6.0	6.5	5.5
DCY052	1/4		8.5	8.0	6.0	8.5	9.5	9.0	11.5	10.0	9.5	8.0
DCY052S		1/4	8.5	8.0	6.0	8.5	9.5	9.0	11.5	10.0	9.5	8.0
DCY053	3/8		23.0	22.0	16.0	23.5	9.5	9.0	11.5	10.0	9.5	8.0
DCY053S		3/8	23.0	22.0	16.0	23.5	9.5	9.0	11.5	10.0	9.5	8.0
DCY082	1/4		9.0	8.5	6.5	9.0	15.0	14.5	17.0	15.5	14.5	13.5
DCY082S		1/4	9.0	8.5	6.5	9.0	15.0	14.5	17.0	15.5	14.5	13.5
DCY083	3/8		24.0	23.0	17.0	24.5	15.0	14.5	17.0	15.5	14.5	13.5
DCY083S		3/8	24.0	23.0	17.0	24.5	15.0	14.5	17.0	15.5	14.5	13.5
DCY084	1/2		38.0	37.0	30.0	39.5	15.0	14.5	17.0	15.5	14.5	13.5
DCY084S		1/2	38.0	37.0	30.0	39.5	15.0	14.5	17.0	15.5	14.5	13.5
DCY162	1/4		9.0	8.5	6.5	9.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY162S		1/4	9.0	8.5	6.5	9.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY163	3/8		24.5	24.0	18.0	25.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY163S		3/8	24.5	24.0	18.0	25.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY164	1/2		41.5	40.0	32.0	43.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY164S		1/2	41.5	40.0	32.0	43.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY165	5/8		68.0	66.0	50.0	70.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY165S		5/8	68.0	66.0	50.0	70.0	40.0	34.0	50.0	37.0	38.0	31.0
DCY302	1/4		9.0	8.5	6.5	9.0	70.0	61.0	80.5	69.0	69.5	56.0